

H.C.B-A2345 FLEXIBLE HEAD CROW FOOT SPANNER KIT (Dr. 1/2?) (9 PCS)



* 230 degree flexible head, plus can use with T-bar, F-Bar, extension bar, and ratchet wrench for accessing more limited space, such as fuel line in engine bay, fuel line, brake line, and so on. * Heat treated, hardened and chrome plated with fully polished mirror finish.

Rating: Not Rated Yet

Price:

Sales price:

Discount:

[Ask a question about this product](#)

Manufacturer: [HCB Specialty Tools](#)

Description

Product Description:

CHT

CHT SUBMERSIBLE SONAR/CHIRP SPANNER KIT (p. 427) (2PCS)

Unit 20: Jamboree
Country of Origin:-
Tokyo
Brand:-
Unit 20
Product Specifications of various

^aSpecial rates for work and travel.

^aCompounds 1a–12^a. ¹H NMR (400 MHz, CDCl₃) δ: 1.0–1.5 (m, 1H), 1.5–2.0 (m, 1H), 2.0–2.5 (m, 1H), 2.5–3.0 (m, 1H), 3.0–3.5 (m, 1H), 3.5–4.0 (m, 1H), 4.0–4.5 (m, 1H), 4.5–5.0 (m, 1H), 5.0–5.5 (m, 1H), 5.5–6.0 (m, 1H), 6.0–6.5 (m, 1H), 6.5–7.0 (m, 1H), 7.0–7.5 (m, 1H), 7.5–8.0 (m, 1H), 8.0–8.5 (m, 1H), 8.5–9.0 (m, 1H), 9.0–9.5 (m, 1H), 9.5–10.0 (m, 1H), 10.0–10.5 (m, 1H), 10.5–11.0 (m, 1H), 11.0–11.5 (m, 1H), 11.5–12.0 (m, 1H), 12.0–12.5 (m, 1H), 12.5–13.0 (m, 1H), 13.0–13.5 (m, 1H), 13.5–14.0 (m, 1H), 14.0–14.5 (m, 1H), 14.5–15.0 (m, 1H), 15.0–15.5 (m, 1H), 15.5–16.0 (m, 1H), 16.0–16.5 (m, 1H), 16.5–17.0 (m, 1H), 17.0–17.5 (m, 1H), 17.5–18.0 (m, 1H), 18.0–18.5 (m, 1H), 18.5–19.0 (m, 1H), 19.0–19.5 (m, 1H), 19.5–20.0 (m, 1H), 20.0–20.5 (m, 1H), 20.5–21.0 (m, 1H), 21.0–21.5 (m, 1H), 21.5–22.0 (m, 1H), 22.0–22.5 (m, 1H), 22.5–23.0 (m, 1H), 23.0–23.5 (m, 1H), 23.5–24.0 (m, 1H), 24.0–24.5 (m, 1H), 24.5–25.0 (m, 1H), 25.0–25.5 (m, 1H), 25.5–26.0 (m, 1H), 26.0–26.5 (m, 1H), 26.5–27.0 (m, 1H), 27.0–27.5 (m, 1H), 27.5–28.0 (m, 1H), 28.0–28.5 (m, 1H), 28.5–29.0 (m, 1H), 29.0–29.5 (m, 1H), 29.5–30.0 (m, 1H), 30.0–30.5 (m, 1H), 30.5–31.0 (m, 1H), 31.0–31.5 (m, 1H), 31.5–32.0 (m, 1H), 32.0–32.5 (m, 1H), 32.5–33.0 (m, 1H), 33.0–33.5 (m, 1H), 33.5–34.0 (m, 1H), 34.0–34.5 (m, 1H), 34.5–35.0 (m, 1H), 35.0–35.5 (m, 1H), 35.5–36.0 (m, 1H), 36.0–36.5 (m, 1H), 36.5–37.0 (m, 1H), 37.0–37.5 (m, 1H), 37.5–38.0 (m, 1H), 38.0–38.5 (m, 1H), 38.5–39.0 (m, 1H), 39.0–39.5 (m, 1H), 39.5–40.0 (m, 1H), 40.0–40.5 (m, 1H), 40.5–41.0 (m, 1H), 41.0–41.5 (m, 1H), 41.5–42.0 (m, 1H), 42.0–42.5 (m, 1H), 42.5–43.0 (m, 1H), 43.0–43.5 (m, 1H), 43.5–44.0 (m, 1H), 44.0–44.5 (m, 1H), 44.5–45.0 (m, 1H), 45.0–45.5 (m, 1H), 45.5–46.0 (m, 1H), 46.0–46.5 (m, 1H), 46.5–47.0 (m, 1H), 47.0–47.5 (m, 1H), 47.5–48.0 (m, 1H), 48.0–48.5 (m, 1H), 48.5–49.0 (m, 1H), 49.0–49.5 (m, 1H), 49.5–50.0 (m, 1H), 50.0–50.5 (m, 1H), 50.5–51.0 (m, 1H), 51.0–51.5 (m, 1H), 51.5–52.0 (m, 1H), 52.0–52.5 (m, 1H), 52.5–53.0 (m, 1H), 53.0–53.5 (m, 1H), 53.5–54.0 (m, 1H), 54.0–54.5 (m, 1H), 54.5–55.0 (m, 1H), 55.0–55.5 (m, 1H), 55.5–56.0 (m, 1H), 56.0–56.5 (m, 1H), 56.5–57.0 (m, 1H), 57.0–57.5 (m, 1H), 57.5–58.0 (m, 1H), 58.0–58.5 (m, 1H), 58.5–59.0 (m, 1H), 59.0–59.5 (m, 1H), 59.5–60.0 (m, 1H), 60.0–60.5 (m, 1H), 60.5–61.0 (m, 1H), 61.0–61.5 (m, 1H), 61.5–62.0 (m, 1H), 62.0–62.5 (m, 1H), 62.5–63.0 (m, 1H), 63.0–63.5 (m, 1H), 63.5–64.0 (m, 1H), 64.0–64.5 (m, 1H), 64.5–65.0 (m, 1H), 65.0–65.5 (m, 1H), 65.5–66.0 (m, 1H), 66.0–66.5 (m, 1H), 66.5–67.0 (m, 1H), 67.0–67.5 (m, 1H), 67.5–68.0 (m, 1H), 68.0–68.5 (m, 1H), 68.5–69.0 (m, 1H), 69.0–69.5 (m, 1H), 69.5–70.0 (m, 1H), 70.0–70.5 (m, 1H), 70.5–71.0 (m, 1H), 71.0–71.5 (m, 1H), 71.5–72.0 (m, 1H), 72.0–72.5 (m, 1H), 72.5–73.0 (m, 1H), 73.0–73.5 (m, 1H), 73.5–74.0 (m, 1H), 74.0–74.5 (m, 1H), 74.5–75.0 (m, 1H), 75.0–75.5 (m, 1H), 75.5–76.0 (m, 1H), 76.0–76.5 (m, 1H), 76.5–77.0 (m, 1H), 77.0–77.5 (m, 1H), 77.5–78.0 (m, 1H), 78.0–78.5 (m, 1H), 78.5–79.0 (m, 1H), 79.0–79.5 (m, 1H), 79.5–80.0 (m, 1H), 80.0–80.5 (m, 1H), 80.5–81.0 (m, 1H), 81.0–81.5 (m, 1H), 81.5–82.0 (m, 1H), 82.0–82.5 (m, 1H), 82.5–83.0 (m, 1H), 83.0–83.5 (m, 1H), 83.5–84.0 (m, 1H), 84.0–84.5 (m, 1H), 84.5–85.0 (m, 1H), 85.0–85.5 (m, 1H), 85.5–86.0 (m, 1H), 86.0–86.5 (m, 1H), 86.5–87.0 (m, 1H), 87.0–87.5 (m, 1H), 87.5–88.0 (m, 1H), 88.0–88.5 (m, 1H), 88.5–89.0 (m, 1H), 89.0–89.5 (m, 1H), 89.5–90.0 (m, 1H), 90.0–90.5 (m, 1H), 90.5–91.0 (m, 1H), 91.0–91.5 (m, 1H), 91.5–92.0 (m, 1H), 92.0–92.5 (m, 1H), 92.5–93.0 (m, 1H), 93.0–93.5 (m, 1H), 93.5–94.0 (m, 1H), 94.0–94.5 (m, 1H), 94.5–95.0 (m, 1H), 95.0–95.5 (m, 1H), 95.5–96.0 (m, 1H), 96.0–96.5 (m, 1H), 96.5–97.0 (m, 1H), 97.0–97.5 (m, 1H), 97.5–98.0 (m, 1H), 98.0–98.5 (m, 1H), 98.5–99.0 (m, 1H), 99.0–99.5 (m, 1H), 99.5–100.0 (m, 1H), 100.0–100.5 (m, 1H), 100.5–101.0 (m, 1H), 101.0–101.5 (m, 1H), 101.5–102.0 (m, 1H), 102.0–102.5 (m, 1H), 102.5–103.0 (m, 1H), 103.0–103.5 (m, 1H), 103.5–104.0 (m, 1H), 104.0–104.5 (m, 1H), 104.5–105.0 (m, 1H), 105.0–105.5 (m, 1H), 105.5–106.0 (m, 1H), 106.0–106.5 (m, 1H), 106.5–107.0 (m, 1H), 107.0–107.5 (m, 1H), 107.5–108.0 (m, 1H), 108.0–108.5 (m, 1H), 108.5–109.0 (m, 1H), 109.0–109.5 (m, 1H), 109.5–110.0 (m, 1H), 110.0–110.5 (m, 1H), 110.5–111.0 (m, 1H), 111.0–111.5 (m, 1H), 111.5–112.0 (m, 1H), 112.0–112.5 (m, 1H), 112.5–113.0 (m, 1H), 113.0–113.5 (m, 1H), 113.5–114.0 (m, 1H), 114.0–114.5 (m, 1H), 114.5–115.0 (m, 1H), 115.0–115.5 (m, 1H), 115.5–116.0 (m, 1H), 116.0–116.5 (m, 1H), 116.5–117.0 (m, 1H), 117.0–117.5 (m, 1H), 117.5–118.0 (m, 1H), 118.0–118.5 (m, 1H), 118.5–119.0 (m